



1074 Kenran Industrial Blvd  
 Saint Louis, MO 63137  
 Phone: (800) 381-9968

# HUMCO Electrical

## Speco Speakers

speco technologies [www.specotech.com](http://www.specotech.com) • 1-800-645-5516

### Weatherproof 8-Ohm P.A. Horn Speakers

#### WEATHERPROOF 5" x 8" ALUMINUM P.A. SPEAKER

Freq. resp. ....200 - 15 kHz

Power rating ...15W nom/25W max.

Sensitivity .....110 dB/1W/1M

Impedance ..... 8 Ohms

Size ..... 8" L x 8" W x 5" H



**SPC15R**

#### WEATHERPROOF MARINE 5" x 8" WHITE ABS P.A. SPEAKER

Stainless Steel Hardware  
 & ABS Plastic Base Brackets Pivots 90°

Freq. resp. .... 200 - 15 kHz

Power rating ..... 60W max.

Sensitivity ..... 60W: 120 dB/1W/1M  
 30W: 105 dB/1W/1M

Impedance ..... 8 Ohms

Size ..... 9" L x 8" W x 5" H



30W max. 8 ohms **SPC15RP**  
 30W max. 4 ohms **SPC15RP4**  
 60W max. 8 ohms **SPC60RP**

#### WEATHERPROOF 6 1/2" x 11" WHITE ABS P.A. SPEAKER

Freq. resp. ....200 - 15 kHz

Power rating ...40W max.

Sensitivity .....120 dB/1W/1M

Impedance ..... 8 Ohms

Size ..... 9" L x 6.5" W x 11" H



8 Ohms **SPC40RP** 4 Ohms **SPC40RP4**

#### WEATHERPROOF 12" ALUMINUM P.A. SPEAKER

Freq. resp. ....150 - 15 kHz

Power rating .....30W nom/65W max.

Sensitivity .....110 dB/1W/1M

Impedance ..... 8 Ohms

Size .....12" Dia. x 12" L



**SPC20**

#### WEATHERPROOF 8" x 12" ALUMINUM P.A. SPEAKER

Freq. resp. ....150 - 15 kHz

Power rating .....30W nom/65W max

Sensitivity .....110 dB/1W/1M

Impedance ..... 8 Ohm

Size .....12" Dia. x 12" L



**SPC20R**

#### WEATHERPROOF 15" ALUMINUM P.A. SPEAKER

Freq. resp. ....130 - 15 kHz

Power rating .....40W nom/75W max.

Sensitivity .....120 dB/1W/1M

Impedance ..... 8 Ohms

Size .....15" Dia. x 13" L



**SPC30**