



1074 Kenran Industrial Blvd
 Saint Louis, MO 63137
 Phone: (800) 381-9968

HUMCO Pumps

Honda General Use Pumps

Redesigned Honda **WB20XT3** & **WB30XT3** General Purpose De-Watering Pumps

**Brand New!
 From Honda!**



WB30XT3



FEATURES/BENEFITS

- Honda commercial grade GX Series engine
- Increased efficiency with redesigned impeller and volute
- New styling (fuel tank & frame design)*
- Easier carburetor access thanks to the WB30XT's redesigned frame
- WB30XT housing size reduction requires less water when priming
- 100% Honda designed
- 3-Year Limited Warranty



WB20XT3

SPECIFICATIONS

	WB20XT3	WB30XT3
Engine	Honda GX120	Honda GX160
Displacement	118cc	163cc
Bore and Stroke	2.4" x 1.7"	2.7" x 1.8"
Compression Ratio	8.5:1	9.0:1
Pump Type	Centrifugal, Self-priming	Centrifugal, Self-priming
Volute	Rigid Mounted Cast Iron	Rigid Mounted Cast Iron
Impeller	4 Vane Cast Iron	4 Vane Cast Iron
Priming Time	110 sec. @ 16.4 ft.	150 sec. @ 16.4 ft.
Discharge Capacity	164 gal./min.	290 gal./min.
Suction Port Diameter	2" NPT	3" NPT
Total Head Lift	105 ft.	85 ft.
Suction Head Lift	25 ft.	25 ft.
Maximum Pressure	45 psi	37 psi
Dimensions (LxWxH)	19.3" x 14.4" x 16.5"	20.1" x 15.2" x 17.9"
Dry Weight	44 lb.	57 lb.
3-Year Limited Warranty	Standard	Standard



HONDA PUMPS

pumps.honda.com



*Frame design styling applies to WB30XT3 only.